




CHARACTERISTIC CURVES

Models: MLX4, MLXW4, MLN4


MRLX4¹, MRLXW4¹, MRLN4¹

Page Number	106-021
Effective	Dec 2005
Replaces	Aug 2005
Section	106


600 RPM




MLN4 - 150 PSI MAX.




500 RPM




MLN4 - 150 PSI MAX.




400 RPM




MLN4 - 150 PSI MAX.



350 RPM



MLN4 - 150 PSI MAX.







¹ 'MRL' models have a low displacement liner – flow rate and horsepower are about 75% of above curves.

NOTE: Blackmer Characteristic Curves are based on Brake Horsepower (BHp). To determine Motor Horsepower, drive train inefficiencies must be added to the BHP.

Actual capacities are dependent upon the vapor pressure of the liquid and the inlet conditions of the system.

CHARACTERISTIC CURVES

Models: MLX4, MLXW4, MLN4, MRLX4¹, MRLXW4¹, MRLN4¹



¹ 'MRL' models have a low displacement liner – flow rate and horsepower are about 75% of above curves.

NOTE: Blackmer Characteristic Curves are based on Brake Horsepower (BHp). To determine Motor Horsepower, drive train inefficiencies must be added to the BHP.

Actual capacities are dependent upon the vapor pressure of the liquid and the inlet conditions of the system.

