



**MATERIALS OF CONSTRUCTION**  
**Models: BV0.75, BV1, BV1.25A,**  
**BV1.50A, BV2A**

Page Number	501-099
Effective	MAY 2006
Replaces	OCT 2005
Section	501

PART NAME	STANDARD MATERIALS	AVAILABLE OPTIONS
Cap, Cover, Body	Ductile Iron: ASTM A536, 18%	
Adjusting Stud & Nut Assy. / Screw	Steel	
Valve	Cast Iron: ASTM A48	
O-Rings	Buna-N	
Spring Guide	Steel	
Spring	Plated Steel	
Spring Ranges		
BV0.75, BV1	Range 71-100 psi (4.90-6.89 bar). Factory Set at 95 psi (6.55 bar) differential pressure - unless otherwise specified.	20-40 psi (1.38-2.76 bar) <sup>1</sup> 41-70 psi (2.83-4.83 bar) <sup>1</sup> 101-125 psi (6.96-8.62 bar) <sup>1</sup>
BV1.25A, BV1.50A	Range 71-125 psi (4.90-8.62 bar). Factory Set at 125 psi (8.62 bar) differential pressure - unless otherwise specified)	20-40 psi (1.38-2.76 bar) <sup>1</sup> 41-70 psi (2.83-4.83 bar) <sup>1</sup> 126-165 psi (8.69-11.38 bar) <sup>1, 2</sup>
BV2A	Range 91-125 psi (6.28-8.62 bar). Factory Set at 125 psi (8.62 bar) differential pressure - unless otherwise specified)	20-40 psi (1.38-2.76 bar) <sup>1</sup> 41-70 psi (2.83-4.83 bar) <sup>1</sup> 71-90 psi (4.90-6.21 bar) <sup>1</sup> 126-150 psi (8.69-10.34 bar) <sup>1, 3</sup>

<sup>1</sup> Optional Springs are set at the midpoint of the range by the factory unless otherwise specified.

<sup>2</sup> Use with pumps rated over 125 psi (8.62 bar) differential pressure.

<sup>3</sup> Non-U.L. Listed, all others are U.L. listed for LPG and NH<sub>3</sub> Service

**PIPE CONNECTIONS**

Model	STANDARD MATERIALS	AVAILABLE OPTIONS
BV0.75	¾" NPT Tapped Ports	
BV1	1" NPT Tapped Ports	
BV1.25A	1 ¼" NPT Tapped Ports	
BV1.50A	1 ½" NPT Tapped Ports	
BV2A	<b>Two 2" NPT Flanges</b> Ductile Iron: ASTM A536, 18%	<b>Two 2" Weld Flanges</b> Steel: ASTM A216 WCB <b>2" Weld x 2" Weld EI Flanges</b> Steel: ASTM A216 WCB

**OPERATING LIMITS**

Maximum Differential Pressure	125 psi (8.62 Bar) 165 psi (11.38 Bar) (BV1.25A, BV1.5A with 126-165 psi spring only) 150 psi (10.34 Bar) (BV2A with 126-150 psi spring only, for non-U.L. Applications)
Maximum Working Pressure	350 psi (24.13 Bar) 390 psi (26.90 Bar) (BV1.25A, BV1.5A with 126-165 psi spring only)