



MATERIALS OF CONSTRUCTION
 Models: LGLD2E, LGLD3E

Page Number 501-094
Effective Nov 2001
Replaces 501/94 Apr 89
Section 501

PART NAME	STANDARD MATERIALS	AVAILABLE OPTIONS
Casing, Heads, Relief Valve Cover	Ductile Iron: ASTM A536, 18%	
Discs, Liner	Cast Iron: ASTM A48	
Bearing Covers	Steel	
Bearings	Ball (Single Row), Grease Lubricated	
Bearing Locknut and Lockwasher	Steel	
Rotor & Shaft	Double End Keyed Shaft, 6-Vane Rotor	
Rotor	Ductile Iron: ASTM A536	
Shaft	LGLD2E High Tensile Steel AISI 41L40 or Equivalent	
	LGLD3E High Tensile Steel AISI 1050 or Equivalent	
Relief Valve	Cast Iron: ASTM A48	Ni-plated Cast Iron
Relief Valve Spring	Plated Steel	
Relief Valve Spring Setting	150 psi (10.34 Bar) Differential Pressure Non-Adjustable	
O-Rings: Other than Mechanical Seal	Buna-N	
Gaskets: Bearing Cover	Fiber	
Vanes	Duravane – Full Size with Stainless Steel Wear Plate	
Push Rods	Case Hardened Steel	
Mechanical Seals		
Stationary O-Ring	Buna-N	
Stationary Seat	Hardened Steel	
Rotating O-Ring	Buna-N	
Rotating Seal Face	Carbon	
Seal Jacket	Plated Steel	
Seal Spring	Stainless Steel	
Companion Flanges	LGLD2E Two 2" NPT Flanges, Ductile Iron: ASTM A536, 18%	Two 2" Weld Flanges, Steel: ASTM A216 WCB
	LGLD3E Two 3" NPT Flanges, Ductile Iron: ASTM A536, 18%	Two 3" Weld Flanges, Steel: ASTM A216 WCB
Gage Ports	1/4" NPT Tapped	

OPERATING LIMITS

Maximum Differential Pressure	150 psi (10.34 Bar)
Maximum Working Pressure	350 psi (24.13 Bar) for LPG and NH ₃ service (Limited by U.L. and NFPA 58)